amaverick sport x rc

HIGHLIGHTS

PLATFORM FEATURES

- 230 cm wheelbase
- 38 cm of ground clearance
- 37.5 cm suspension travel
- **Dynamic Power Steering** (DPS[™])
- 14-in. cast-aluminum wheels

meaningful functionalities

- $SPORT \, / \, ECO^{\scriptscriptstyle\mathsf{TM}} \, \, modes$
- Premium half doors

Sturdy engine and

Can-Am design

transmission Enhanced comfort and

Mudguards

DARING

SPECIFIC TO X rc PACKAGE

- 162.6 cm wide with Arched A-arms
- Smart-Lok** front differential FOX† 2.5 PODIUM† QS3 Piggyback shocks
- 30-in. Maxxis† Liberty† tires
- 2,041 kg winch with synthetic cable
- Rear sport bumper, front anchor
- HMWPE front skid plate and rock sliders
- UHMWPE front and rear suspension arm protectors
- 7.6-in. digital display with keypad
- Premium tail light

PRECISE

- · Easy handling and capabilities
- Suspensions designed for performance
- Ultra-resistant chassis

CONFIDENT

- Perfectly tuned
- Enhanced protection
- More adventure and less maintenance





Carbon Black & Orange Crush / 1000R

Front Tires

Rear Tires

Towing capacity

Fuel Capacity

Maxxis Liberty

30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)

> Maxxis Liberty 30 x 11 x 14 in.

> > 680 kg 38 L

| ENGINES | 1000R | | |
|----------------------|---|--|--|
| Туре | 100 hp, Rotax® 976 cc, V-twin, liquid cooled | | |
| Fuel Delivery System | Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI) | | |
| Transmission | Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P | | |
| Drive Train | Lockable front differential with exclusive Smart-Lok* technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD ROCK / 4WD TRAIL *Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry | | |
| Driving Assistance | Electronic Hill Descent Control SPORT / ECO™ modes | | |
| Power Steering | Dynamic Power Steering (DPS) | | |
| SUSPENSIONS | | | |
| Front Suspension | Arched double A-arm with sway bar / 37.5 cm travel | | |
| Front Shocks | FOX 2.5 PODIUM Piggyback with QS3 compression adjustment | | |
| Rear Suspension | Arched TTA with sway bar / 37.5 cm travel | | |
| Rear Shocks | FOX 2.5 PODIUM Piggyback with QS3 compression adjustment | | |
| BRAKES | | | |
| Front | Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers | | |
| Rear | Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers | | |

| | (76.2 x 27.9 x 35.6 cm) | | |
|-----------------------|---|--|--|
| Wheels | 14 in. (35.6 cm) cast-aluminum | | |
| DIMENSIONS / | CAPACITIES | | |
| LxWxH | 309.8 x 162.6 x 188.6 cm | | |
| Wheelbase | 230.1 cm | | |
| Ground Clearance | 38.1 cm | | |
| Dry Weight | 722.6 kg | | |
| Chassis / Cage | Profiled cage ROPS approved | | |
| Cargo Box Capacity | 136 kg | | |
| Storage Capacity | Total: 20.2 L Glove Box: 15.6 L Driver storage: 1.5 L Center console and Cup holders: 3.1 L | | |

| FEATURES | | | |
|-----------------|--|----------------|---|
| Gauge | 7.6 in. (19.3 cm) wide digital display with keypad: | Winch | 2,041 kg winch with synthetic rope |
| | Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, SPORT / ECO modes, seat belt, diagnostics, clock, battery voltage, engine temperature | Steering Wheel | Adjustable tilt steering |
| Instrumentation | Lighter type DC outlet in console (20 A) | Protection | Integrated front steel bumper, rear sport bumper, premium half doors, mudguards, front tow hook, full skid plate, UHMWPE rock sliders, HMWPE skid plates: differential and front skid plate / front and rear suspension arm |
| Magneto | 650 W | | |
| Lighting | Two 55 W reflectors with unique Can-Am LED signature and LED tail lights with halo glow effect | Hitch Type | 2 in. hitch receiver |

| WARRANTY | | |
|----------|---------|--|
| Factory | 2 years | |



