

2020 OUTLANDER™ PRO 650

HIGHLIGHTS

- Rotax® V-twin engine
- Intelligent Throttle Control (iTC™) with riding modes
- Arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with extra low L gear
- Tri-Mode Dynamic Power Steering (DPS)
- 26-in. Carlisle ACT HD 6-ply tires
- Visco-Lok QE auto-locking front differential
- 750 kg towing capacity
- RF Digitally Encoded Security System (D.E.S.S.)
- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- 21.4 L water-resistant rear compartment
- Reinforced seat skin
- Increased ground clearance
- Relocated air intakes
- Mudguards



Green

ENGINES

650

Type	59 hp, Rotax 649.6 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra low L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar 23.3 cm travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 25.1 cm travel
Rear Shocks	Oil

BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

FEATURES

Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	Prewired for available winch	Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Protection	Mudguards	Seat	Reinforced seat skin
		Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)

WARRANTY

Factory	2 years
---------	---------

TIRES / WHEELS

Front Tires	Carlisle† ACT HD 26 x 8 x 12-in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle† ACT HD 26 x 10 x 12-in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. steel

DIMENSIONS / CAPACITIES

L x W x H	218.4 x 122 x 126 cm
Wheelbase	129.5 cm
Ground Clearance	30.5 cm
Seat Height	87.7 cm
Dry Weight*	341 kg
Rack Capacity	Front: 45 kg Rear: 90 kg
Storage Capacity	Rear: 21.4 L
Towing Capacity	750 kg
Fuel Capacity	20.5 L