

## **HIGHLIGHTS**

- Rotax<sup>®</sup> V-Twin engine
- Intelligent Throttle Control (iTC<sup>™</sup>) with riding modes
  Front and rear FOX† PODIUM† 1.5 RC2 shocks
- Continuously Variable Transmission (CVT) with engine braking
  Tri-Mode Dynamic Power Steering (DPS)
- Front, center & footwell aluminum skid plates
  A-arms MWPE protectors

- 14-in. cast-aluminum (35.6 cm) beadlock wheels • 26-in. (66 cm) ITP† Terracross radial tires
- Aluminum sport bumper with aluminum pre-runner and top brace • High-strength, multifunction racks with LinQ™ quick-attach accessory system
- 650-W magneto
- 5.7-gal (21.4 L) water-resistant rear compartment
- X package coloration
- Visco-4Lok front differential
- Aluminum taper-profile handlebar with full wrap handguards



### ENGINE

Rear

ENGINE	
Туре	68 k W (91 hp), Rotax® 976 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD / Lock 4WD with Visco-4Lok front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel
Front Shocks	FOX† 1.5 PODIUM† RC2
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel
Rear Shocks	FOX† 1.5 PODIUM† RC2
TIRES / WHEELS	
Front Tires	ITP† Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm)
Rear Tires	ITP† Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)
Wheels	14-in. (35.6 cm) cast-aluminum beadlock
BRAKES	
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers

### **DIMENSIONS / CAPACITIES**

Estimated Dry Weight *	826 lb (375 kg)
L×W×H	86 x 48 x 49.5 in. (218.4 x 121.9 x 126 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	11 in. (27.9 cm)
Seat Height	34.5 in. (87.7 cm)
Rack Capacity	Rear: 200 lb (90 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)
Towing Capacity	1,650 lb (750 kg)
Fuel Capacity	5.4 gal (20.5 L)

#### FEATURES

LAIONES	
Gauge	7.6-in wide digital display: Speedometer, tachometer, odometer, trips & hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge, clock
Instrumentation	Lighter type DC Outlet in console, standard connector in the back (15-A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Winch	Prewired for available winch
Seat	Standard
Protection	Aluminum front bumper with pre-runner and top brace Aluminum taper-profile handlebar with full wrap handguards Front, center & footwell aluminum skid plates A-arms HMWPE protectors Mudquards

# WARRANTY

Factory warranty

2-year BRP limited warranty

©2021 Bombardier Recreational Products Inc (BRP). All rights reserved. "<sup>1</sup>, \* and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. \*Base model dry weight shown. \*Visco-Lok is a trademark of GKN Viscodrive GmbH. \*All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right, at any time, to discontinue or change specifications, prices, your dealer. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs dont mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never earry passengers on any ATV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

Single 214 mm disc brake with hydraulic

twin-piston caliper

