



HIGHLIGHTS

- Rotax® snorkeled V-Twin engine with relocated CVT intake and outlet Intelligent Throttle Control (iTC™) with riding modes
- Front and rear FOX† 1.5 PODIUM† QS3 Shocks
- 30 in. (76.6 cm) ITP Cryptid† tires
- 14 in. (35.6 cm) cast-aluminum beadlock wheels
- 3,500-lb (1,588 kg) winch
- Front & central aluminum skid plate
- Heavy-duty front and rear bumpers
- Aluminum taper-profile handlebar with grab handle and full-wrap handguards
- Tri-Mode Dynamic Power Steering (DPS)
- Continuously Variable Transmission (CVT) with Extra Low L-Gear
 Torsional Trailing arm Independent (TTI) rear suspension
- Mudguards
- Multifunction digital gauge
- Painted plastics for premium look
- X-package coloration, graphics and seat cover
 Visco-4Lok front differential



Liquid Titanium & Magma Red

ENGINE	1000R
Туре	68 k W (91 hp), Rotax® 976 cc V-twin, snorkeled, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 2WD / 4WD / Lock 4WD with Visco-4Lok front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar
Front Shocks	FOX† 1.5 PODIUM† QS3
Rear Suspension	Torsional Trailing arm Independent (TTI)
Rear Shocks	FOX† 1.5 PODIUM† QS3
TIRES / WHEELS	
Front Tires	ITP Cryptid 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Rear Tires	ITP Cryptid 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum beadlock
BRAKES	
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

DIMENSIONS / CAPACITIES

Estimated Dry Weight *	991 lb (450 kg)
LxWxH	83 x 50 x 56 in. (224 x 127 x 131 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	12.5 in. (31.8 cm)
Seat Height	36.75 in. (93.3 cm)
Rack Capacity	Rear: 35 lb (16 kg)
Storage Capacity	N/A
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES

TEATOREO	
Gauge	4.5-in. digital display: Speedometer, tachometer, odometer, trip & hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge & clock
Instrumentation	Lighter type DC Outlet in console, standard connector in the back (15-A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	240 W from 4 fender mounted projector beam headlamps (60-W) with tail light / brake light
Winch	3,500-lb (1,588 kg) winch
Seat	Standard
Protection	Front & rear bumpers Aluminum taper-profile handlebar with grab handle and full wrap handguards Mudguards Front & central aluminum skid plate

WARRANTY & EXTENDED SERVICE

	2-year BRP limited warranty
Factory warranty	

