



ROTAX [®] ENGINE	600 ACE Liquid-cooled, four-stroke D.O.H.C.	
Engine details		
Cylinders	2	
Displacement	600 cc	
Bore	74 mm	
Stroke	69.7 mm	
Maximum engine speed	7250 RPM	
Carburation	EFI	
Recommended fuel type	Unleaded	
Minimum octane	95	
Fuel tank	42 liters	

COLOUR

Viper Red/Black

DIMENSIONS

3240 mm	
1200 mm	
1500 mm	
996 mm	
500 mm	
3923 mm	
44 mm	

POWERTRAIN

Gearbox	2F/N/R with push-button reverse		
Drive clutch type	eDrive II		
Driven clutch type	QRS		
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder		

SUSPENSION

Front suspension	LFS	
Front shock	HPG 36	
Rear suspension	EasyRide with adjustment	
Center shock	HPG 36	
Rear shock	HPG 36	

FEATURES

Frame	Radien-X	Heated grips	Standard
Skis	Blade DS+	Gauge	Compact digital display
Seating	Modular, 1-up	Windshield	Extra high with side deflectors
Handlebar	U-type steel with hooks, low grab	Hitch	Standard
	handle	Visor Plug front / rear	Front
Riser block height	145 mm	USB power outlet	Front
Starter	Electric	Air radiator with fan	Yes
Reverse	Electromechanical	LinQ attachment	Multi-LinQ plate
Heated throttle lever	Standard		

* Vehicle overall length without snowflap.

©2022 Bombardier Recreational Products Inc., (BRP). All rights reserved. ™,* and the BRP logo are trademarks of BRP or its affiliates. *All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.

