MY23 TRAXTER X MR HDI0



Liquid Titanium & Magma Red

ENGINE

Туре	61 kW (82 hp) / 69 lb-ft, Rotax® 976 cc, V-twin, liquid cooled with strategically positioned engine air intake
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PRO-TORQ CVT Transmission with Quick Response System (QRS), Electronic Drive Belt Protection, lower gearing ratio and high airflow ventilation with strategically positioned CVT air intake and exhaust Extra-L / H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD TRAIL / 4WD MUD with exclusive Smart-Lok * technology. *Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry
Driving Assistance	Electronic Hill Descent Control ECO™ / ECO™ Off / Work modes Brake holding mechanism
Power Steering	Dynamic Power Steering (DPS™)
SUSPENSIONS	
Front Suspension	Arched double A-arm with swaybar / 12 in. (30.5 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	Arched TTA with external sway bar / 12 in. (30.5 cm) travel
Rear Shocks	Twin tube gas charged shocks

TIRES / WHEELS

Rear

Front & Rear Tires	XPS Swamp Force 30 x 9 / 11 x 14 in. (76.2 x 22.9 / 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum
BRAKES	
Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers

Dual 220 mm disc brakes with hydraulic single-piston calipers

HIGHLIGHTS

- Smart-Lok front differential Strategically positioned engine air intake and CVT inlet / outlet
- Brake holding mechanism
- VERSA-PRO bolster bench seat, reinforced seat skin featuring X package trims and adjustable driver seat
- 7.6 in. (19.3 cm) digital display with keypad
 64 in. (162.5 cm) wide with Arched A-arm
- LED Signature
 30 in. (76.2 cm) XPS Swamp Force tires
- 4,500-lb (2,041 kg) winch Heavy-duty front steel bumper
- Aluminum rock slider
 HMWPE full skid plate
- Horn & side mirrors

Cage	Profiled cage.
	ROPS approved
Estimated Dry Weight *	1,746 lb (792 kg)
LxWxH	129.4 x 64 x 82 in.
	(328.6 x 162.6 x 208.3 cm)
Wheelbase	83 in. (211.5 cm)
Ground Clearance	15 in. (38.1 cm)
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)
Cargo Box Capacity	1,000 lb (454 kg)
Power tilt bed	N/A
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity	Total: 16.2 gal (61.3 L)
Towing Capacity	2,500 lb (1136 kg)
Payload Capacity	1,500 lb (680 kg)
Fuel Capacity	10.6 gal (40 L)
Person Capacity	3

FEATURES

Gauge	7.6 in. (19.3 cm) wide digital display with keypad
Battery	12-V (30 amp/h)
Magneto	650-W
Instrumentation	DC outlet (10-A) USB Port (10-A) x 2
Lighting	Front lighting output 140 W LED signature LED tail lights
Winch	Relocated 4,500-lb (2,041 kg) winch with synthetic rope and roller fairlead
Seat	VERSA-PRO bolster bench seats with passenger seats flipping up, adjustable driver seat, underside hooks, reinforced seat skin featuring X package trims
Steering Wheel	Adjustable tilt steering
Protection	Heavy-duty front steel bumper HMWPE full skid plate Aluminum rock sliders Mudguards
Hitch Type	2-in hitch receiver
WARRANTY	

2-year BRP limited warranty Factory warranty



DIMENSIONS / CAPACITIES

©2022 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, * and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †All trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional accurrence of the second equipment.

