2023 DEFENDER MAX XT





Oxford Blue HD9 / HD10 Stone Gray HD9 / HD10

Mossy Oak® Break-Up Country Camo HD9 / HD10

ENGINES	HD9	HD10
Туре	65 hp/59 lb-ft , Rotax [®] 976 cc, V-twin, liquid-cooled	82 hp/69 lb-ft, Rotax [®] 976 cc, V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
Transmission	PRO-TORQ CVT Transmission with Quick Response System (QRS), high-airflow ventilation and Electronic Drive Belt Protection Extra L/H/N/R/P	
Drive Train	Selectable Turf Mode/2WD/4 with Visco-Lok [†] auto-locking fr	
Driving Assistance	Electronic Hill Descent Control ECO™/ECO™ Off/Work modes	
Power Steering	Dynamic Power Steering (DPS	тм)

Double A-arm/10 in. (25.4 cm) travel	Arched double A-arm/11 in. (27.9 cm) travel
Twin tube gas-charged shocks	
TTA with external sway bar/ 10 in. (25.4 cm) travel	Arched TTA with external sway bar/11 in. (27.9 cm) travel
Twin tube gas-charged shocks	5
	(25.4 cm) travel Twin tube gas-charged shocks TTA with external sway bar/ 10 in. (25.4 cm) travel

TIRES & WHEELS

Front/Rear Tires	XPS Trail Force 27 x 9/11 x 14 in.	XPS Trail King 27 x 9/11 x 14 in.
Wheels	14 in. cast-aluminum	

BRAKES

Front Dual 220 mm disc brakes with hydraulic twin-piston calipers Rear Dual 220 mm disc brakes with hydraulic twin-piston calipers Brake holding mechanism

PACKAGE HIGHLIGHTS

HD9	HD10
 Brake holding mechanism 	Brake holding mechanism
VERSA-PRO bolster bench seat with reinforced XT seat skin and adjustable driver seat	VERSA-PRO bolster bench seat with reinforced XT seat skin and adjustable driver seat
 4,500-lb (2,014 kg) winch 	64 in. wide with Arched A-arm
 XT front bumper 	 27 in. XPS Trail King tires
Full hard roof	• 4,500-lb (2,014 kg) winch
 HMWPE full skid plate 	XT front bumper
	Full hard roof

· HMWPE full skid plate

DIMENSIONS & CAPACITIES	HD9	HD10
Cage	Profiled cage, ROPS approved	
Estimated Dry Weight	1,902 lb (863 kg)	1,928 lb (875 kg)
L×W×H	158.3 x 63.5 x 76 in. (402 x 161.2 x 193 cm)	158.3 x 64 x 79.5 in. (402 x 162.5 x 202 cm)
Wheelbase	115.5 in. (294 cm)	-
Ground Clearance	11 in. (28 cm)	13 in. (33 cm)
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4	x 30.5 cm)
Cargo Box Capacity	1,000 lb (454 kg)/California on	ly: 600 lb (272.2 kg)
Power Tilt Bed	N/A	
Tailgate Load Capacity	250 lb (113.4 kg)	
Storage Capacity	Total: 16.9 gal (63.9 L)	
Towing Capacity	2,500 lb (1,134 kg)	
Payload Capacity	1,700 lb (771 kg)	
Fuel Capacity	10.6 gal (40 L)	
Person Capacity	6	

FEATURES

Gauge	4.5 in. wide digital display
Battery	12 V (30 amp/h)
Magneto	650 W
Instrumentation	DC outlet (10-A), USB Port (10-A) x 2
Lighting	Front lighting output 140 W, LED tail lights
Winch	4,500-lb (2,041 kg) winch with roller fairlead
Seat	VERSA-PRO bolster bench seats with passenger seats flipping up. Adjustable driver seat, underside hooks, reinforced XT seat skin.
Steering Wheel	Adjustable tilt steering
Protection	XT front bumper, HMWPE full skid plate, 2-piece full hard roof
Hitch Type	2 in. hitch receiver

WARRANTY & EXTENDED SERVICE

Factory Warranty	1 year BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



© 2022 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. †Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety, wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding, alcohol and drugs don't mix. SSVs are for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold hand grips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. Ride responsibly.

