

2026 MAVERICK X RC TURBO RR



Loft Green Satin

PACKAGE HIGHLIGHTS

- Smart-Lok™ front differential
- FOX† 3.0 PODIUM RC2† shocks with bypass
- Belt monitoring system
- 850-W Magneto
- 4.5 in. wide digital display with keypad & 10.25 in. touchscreen display
- X-package graphics/seats
- 4-point harness with shoulder pads
- Can-Am LED signature
- 15 in. aluminum beadlock wheels
- 32 in. XPS Hammer King tires
- Front bumper, half-doors, aluminum roof, intrusion bar
- Front tow hook
- 4,500 lb (2,041 kg) winch with synthetic rope
- HMWPE differential and under bumper skid plates
- HMWPE front and rear suspension arm
- UHMWPE rock sliders
- RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
- Horn with carling

ENGINES		Turbo RR
Type	200 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and high-performance air filter	
Fuel Delivery System	Intelligent Throttle Control (iTCTM) with Electronic Fuel Injection (EFI)	
Transmission	pDrive primary and Quick Response System X (QRS-X) CVT with high airflow L / H / N / R / P	
Drive Train	Lockable front differential with exclusive Smart-Lok* technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD ROCK / 4WD TRAIL	
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)	
SUSPENSIONS		
Front Suspension	Trophy truck inspired double arched A-arm with sway bar / 22 in. (55.9 cm) suspension travel	
Front Shocks	FOX† 2.5 PODIUM RC2† Piggyback with bypass, dual speed compression and rebound adjustments	
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links / 24 in. (61 cm) suspension travel	
Rear Shocks	FOX† 3.0 PODIUM RC2† with bypass, dual speed compression and rebound adjustments	
TIRES / WHEELS		
Front / Rear Tires	XPS Hammer King 32 x 10 x 15 in.	
Wheels	15 in. cast-aluminum beadlock	
BRAKES		
Front	Dual 262 mm disc brakes with hydraulic twin-piston calipers	
Rear	Dual 248 mm disc brakes with hydraulic twin-piston calipers	

DIMENSIONS / CAPACITIES	
Cage	Dual-phase 980 steel
Estimated Dry Weight*	1,843 lb (836 kg)
L x W x H	134.5 x 72.8 x 68.5 in. (341.6 x 184.9 x 174 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	16 in. (40.6 cm)
Cargo Box Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L)
Fuel Capacity	10.5 gal (40 L)

FEATURES	
Gauge	4.5 in. wide digital display with keypad & 10.25 in. touchscreen display
Magneto	850-W
Instrumentation	DC outlet (10-A)
Lighting	LED Headlight LED Signature LED tail lights
Winch	4,500 lb (2,041 kg) winch with synthetic rope
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Protection	Front bumper Half-doors Aluminum roof Intrusion bar 4-point harness with shoulder pads UHMWPE rock sliders HMWPE skid plates: Full heavy duty with differential / Under bumper / Front and rear suspension arm Rear tow hook Trailing Arm protector

WARRANTY & EXTENDED SERVICE	
Factory warranty	2-year BRP limited warranty



REQUEST A QUOTE



©2025 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.